


PRINCE WILLIAM COUNTY **Department of Development Services – Building Development Division**

SOLAR ENERGY SYSTEMS SMALL, MICRO INVERTER / AC SYSTEM PLANS LOAD SIDE CONNECTION



0	EQUIPMENT SCHEDULE								
TAG	DESCRIPTION MODEL NUMBER		R	NOTES					
1	SOLAR PV MODULE								
2	PV ARRAY		N	Module	VOC	V	ISC_	R	
3	MICRO INVERTER		MAX INPUT:VDC	MAX INPUT:VDC,ISC MAX PER BRA		ANCHOUTPUT:			
4	J-BOX (IF USED)		BRANCH 1 INVERTER COU	BRANCH 1 INVERTER COUNT BRANCH 2 INVERTER COUNT BRANCH 3 INVERTER COUNT BRANCH 4 INVERTER COUNT					
5	COMBINER		BRANCH 1 INVERTER COU	BRANCH 1 INVERTER COUNT BRANCH 2 INVERTER COUNT BRANCH 3 INVERTER COUNT BRANCH 4 INVERTER COUNT					
6	AC DISCONNECT		VAC	A Rated					
7	SERVICE PANEL		VAC		A Main	A Bus		A Inverter OCPD	
Δ	CONDUIT AND CONDUCTOR SCHEDULE								
TAG	DESCRIPTION OR CONDUCTOR TYPE C		CONDUCTOR GAUGE		JMBER OF CONDUIT/ CABI		LE TYPE	CONDUIT SIZE	
1	Inverter Output Cable BARE COPPER EQ. GRD. COND. (EGC)		Equipment Cut Sheet	Equipme	ment Cut Sheet 1 N/A			N/A	
2	☐ THWN-2 or ☐ XHHW-2 or ☐ RHW-2 INSULATED EGC								
3	Branch OCPD	AMPS				N/A		N/A	
4	Combiner OutputAMPS					N/A		N/A	
5	☐ THWN-2 or ☐ XHE INSULATE	IW-2 or ∐RHW-2 DEGC							
6	GROUNDING ELECTRODE COND.		EXISTING	EXISTING N/A		N/A		N/A	
7	SOLAR BACK-FED OCPAMPS					N/A		N/A	
NOTES									
	NOTES								

	NOTES
1	All labels will be placed in accordance with NEC 690, and 705.
2	Additional labeling is required; see the Solar Energy Systems Plan Submission and Inspection Guidelines for details.
3	The sum of all supply breakers feeding a busbar / conductor cannot exceed 120% of the busbar / conductor rating.
4	Interconnection within the main panel shall be located at the opposite end of the main breaker.